

CANYCOM TRACKED DUMPER S120A



For Construction and Landscaping

Compact tracked dumper with pivoting bucket for different application. Heavy duty rubber tracks and roller system provides a comfortable ride and minimises ground damage. Easy access in narrow job sites & Climb up to 20 degrees with ease.

Max. Payload
1,200kg

Engine
KUBOTA D902

Dumping type
Swivel

Speed
5.6km/h

Dimensions
L2670 / W990 / H2330mm



Comfort as priority.
Good seating position



Wide foot space



Easy to reach
all the control levers



Folding ROPS
For transport and job site with limited height



Wide opening covers
For an easy access to E/G components



Battery switch



Compact



Auxilliary third valve for attachment like self loader etc.



CANYCOM

CHIKUSUI CANYCOM, INC.

HAKATA OFFICE(OVERSEAS DIV.)

Yutoku Bldg 6F, 1-5 Nakagofuku-machi, Hakata, Fukuoka, 812-0035, JAPAN

TEL +81-92-272-1104 FAX +81-92-272-1119

e-mail exinfo@canycom.co.jp



SPECIFICATIONS SHEET FOR S120A

CANYCOM

Machine Mass		kg	1100
Maximum Payload		kN(kgf)	11.8 (1200)
HST Oil Capacity		L	20
Operating Temperature		°C	between -15°C and +40°C
Operating Elevation		m	below 1500 *1
Dimensions			
Overall Length		mm	2670
Overall Width		mm	990
Overall Height		mm	2330
Tumbler Length		mm	1160
Track Tread		mm	760
Minimum Ground Clearance		mm	145
Floor Height		mm	620
Loading Deck			
Inside Dimensions	Length	mm	1340
	Width	mm	890
	Height	mm	490
Payload	Struck	m³ (kg)	0.39 (860)
	Heaped	m³ (kg)	0.59 (1180)
Engine			
Model		Kubota D 902	
Type		4-cycle, Water-cooled Diesel	
Cylinder (Bore X Stroke)		mm	67 X 68
Total Displacement		cm³	898
Rated Output		kW(PS)/rpm	12.9 (17.5) / 2600 *net
Maximum Torque		N•m/rpm	53.5 / 2200 *net
Starting		Electric	
Fuel used		Diesel Fuel	
Fuel Consumption		g/kW•h	254
Fuel Tank Capacity		L	15.0
Lubricating Oil Capacity		L	3.8
Battery Capacity		V/AH	12/52
Performance			
Travel Speed		km/h	0 to 5.6
Minimum Turning Radius		m	1.55
Gradability		Degrees	25 (unloaded)
Drive Train			
Main Transmission		Twin HST	
Steering System		Twin HST - 2 Lever	
Brakes		Internally Expanding	
Dumping System			
Dump System		Swivel Dump	
Hydraulic Pump	Type	Gear Pump	
	Max. Discharge	L/min	10.0
Relief Pressure		MPa(kgf/cm²)	14.78 (150)
Dumping Max. Angle		Degrees	90
Swivel System			
Swivel System		Hydraulic (Twin cylinder)	
Swiveling Angle		°	90(Right) - 90 (Left)

*1 Engine performance is reduced when used above 1500m of elevation.
These specifications are subject to change without notice.