

- The continuous **hydraulic rotation** enables precise positioning during in height demolitions and the double-row thrust bearing ensures high robustness and increases safety.
- The **powerful cylinders** deliver an enormous force thanks to the perfect cinematics.
- A **special teeth profile**, studied to remain sharpen despite wear, maximizes penetration.
- The **twin-pin system** enables larger opening and higher power, even at maximum opening.
- The interchangeable **rebar cutting blades** can be turned 4 times before replacement.

TECHNICAL DATA

		BT.CR.08	BT.CR4.00	
MODEL		CR2	CR4	CR5
ROTATION		Mechanical		
EXCAVATOR WEIGHT	t	03-05	03-06	06-10
TOOL WEIGHT *	kg	240	320	530
OPENING	mm	360/0	440/0	450/0
HEIGHT	mm	1070	1070	1290
HYDRAULIC WORKING PRESSURE	bar	180-220	250	200-250
OIL FLOW	l/min	30-50	65	50-90



- The patented **Speed-Valve** improves productivity and protects the hydraulic system from pressure peaks.

BT.CRR.12

CR5R	CR15R	CR20R	CR26R	CR40R	CR60R	CR80R	CR100R	CR120R
360° Hydraulic								
07-11	16-20	21-26	27-35	45-55	60-70	75-95	100-120	120-140
630	1600	2100	2800	4720	6250	8250	11000	12000
450/0	800/0	1050/0	1100/0	1350/0	1580/0	1800/0	2050/0	2310/320
1315	1800	2030	2200	2800	3020	3400	3200	3300
200-250	280-320	280-320	280-320	280-320	320-350	320-350	320-350	320-350
50-90	130-150	180-220	220-250	250-300	320-350	500-600	600-800	600-800

\* Tool weight does include Mantovanibenne top bracket.



## NOTES

---

---

---

---

---

---

---

---